HP CP1518 DOCTOR BLADE ALIGNMENT FIXTURE

Patent Pending

INSTALLATION INSTRUCTIONS

List of Printers:

HP CM1312, CP1215, CP1515, CP1518

List of OEM Cartridge Part Numbers:

CB540A – Black Cartridge, 2200 Pages @ 5% Coverage
CB541A – Cyan Cartrigde, 1400 Pages @ 5% Coverage
CB542A – Yellow Cartridge 1400 Pages @ 5% Coverage
CB543A – Magenta Cartidge 1400 Pages @ 5% Coverage

Tools and Materials:

HP1518DBSHIM (Purchased separately)
Phillips Screwdriver

Contents:

Fixture (Qty: 1)
User Instructions (Qty: 1)

IMPORTANT: The HP CP1518 Doctor Blade Installation Fixture must be secured to the table with screws or a clamp for proper use.

Step 1

Place the doctor blade shims onto the ends of the doctor blade *(See photo 1).*

PHOTO 1

Step 2

Set the doctor blade on the toner hopper. Install the two screws that hold the doctor blade but do not tighten them. Place the toner hopper onto the toner hopper doctor blade alignment fixture. *(See photo 2).*

PHOTO 2

Step 3

Press down on the red handle until the clamp locks into place. Finish tightening down the doctor blade screws *(See photo 3).*

PHOTO 3

Step 4

Lift red handle to release the clamp. Remove the toner hopper.

Notes

© 2008 Future Graphics, LLC. All rights reserved. Future Graphics (FG) is a distributor of compatible replacement parts and products for imaging equipment. None of FG's products are genuine OEM replacement parts and no affiliation or sponsorship is to be implied between FG and any OEM.